


## BTGOR12





## **PRODUCT FEATURES**


- Open front
- Stainless steel hinged rear doors
- Deck forced refrigeration
- Double glazed glass ends
- Two adjustable glass shelves
- Flat or angled shelves
- Ticket strips on shelves and base
- Under shelf and canopy LED lights
- Integral condenser
- Pull down night blind
- Perspex riser

Maximum shelf load weight 15kg spread evenly Adjustable rear or front venting









## **CABINET DIMENSIONS & SPECIFICATIONS**

Prior to installation see, installation guidelines and ventilation requirements document

																		'				
MODEL	CABINET				SHELVING	OPERATING TEMP	SHELF	BASE TRAY	TOTAL FOOD	DISPLAY M <sup>2</sup>	INTERNAL VOLUME M <sup>3</sup>	FREQUENCY	REFRIGERANT	POWER		ELECTRIC	ECTION CAL POWER 2200MM	VOLTAGE	PACKED FOR SHIPPING			;
	LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]											KW 230V		NZ/AUS 10 AMP			LENGTH [MM]	DEPTH [MM]	HEIGHT [MM]	WEIGHT
BTGOR12	1200	750	1380	273	2 + BASE	3-5	1085 X 440	1145 x 515	123	1.31	0.60	50 Hz	R290	1.39	7.6	3 PIN PLUG	3 PIN PLUG	220- 240V	1300	830	1550	279



