



DXG Series Gourmet Ice Dispenser – up to 27kg

DXG 35 AS Medium gourmet cube 20g, Ø30mm x 34mm



Medium gourmet cube 20g, 30mm dia x H 34mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 27kg daily production rate
- 11kg storage bin capacity
- Air cooled version
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Push button dispensing system: cubes drop directly into consumers glass
- Individual transparent Gourmet crystal clear supercubes
- Horizontal ice evaporator spray-system technology
- Clean alert indicator to clean filter
- Resistant stainless steel exterior
- Simple, reliable electromechanic controls
- Easy access removeable front condenser air filter
- External indicator lights to show operation status
- Includes water and drain hose
















DXG Series Gourmet Ice Dispenser – up to 27kg

DXG 35 AS







MOFFRT

moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia


Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9413 2400 wasales@moffat.com.au



- 1. 13/16" WATER OUTLET
- 2. 3/4" WATER INLET
- 3. 3/4" WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" WATER INLET WATER COOLED UNIT ONLY
- 5. CORD SET

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
29	27	15

Dimensions

Width: 380mm
Depth: 515mm
Height: 1696mm
Nett weight: 51kg
Packed weight: 60kg

Water consumption

Air cooled version: 2.7 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 400W,

10A cordset supplied

No. Circuit wire: 3 Compressor: 790W Energy consumption: 7kW/24hr

Refrigerant type

R134a

Installation distance from wall

Rear 100mm Sides 150mm

Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R ¾"
Cold water: 5-38°C
Pressure: 100-500kPa
Water outlet connection: ؾ"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd