



# Blue Seal Electric Combi Steamer **COMPACT SAPIENS RELOADED** EC611RSDW 6 x 1/1 GN



- Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclima, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat  $30^{\circ} 300^{\circ}C$
- Manual pre-heating
- Auto-reversing fan rotation
- Autoclima with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- · Externally connected hand shower
- USB connection

#### **GENERAL FEATURES**

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces head radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overhear display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

### OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood







**ECOVAPOR** 











# Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC611RSDW 6 x 1/1 GN

#### Dimensions

Width 510mm Depth 800mm Height 880mm Weight 73kg

#### Packed dimensions

Width 570mm Depth 930mm Height 1020mm Weight 82kg

#### **Shelves**

1/1 GN 6 Shelf Spacings 60mm

#### Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

## Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

#### Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

#### Power connection

Total (kW) 7.75 Convection power (kW) 7.5 Rated Current (A) (400V) 12

#### Installation clearances

- rear 50mm - right 500mm\* - left 50mm
- \*Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

# Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection\*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R3/4
- R40 waste water connection

(\*Water softener may be required. Please refer to installation manual for water treatment values.)

## **MOFFRT**®

Australia www.moffat.com.au

New Zealand www.moffat.co.nz

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9413 2400 wasales@moffat.com.au

#### New Zealand Moffat Limited

#### Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone 03-983 6660 Facsimile 03-983 6660 sales@moffat.co.nz

#### Auckland

Telephone 09-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Moffat 1569 / 18.05







Electric power supply cable inlet



Gas inlet and type of thread























an Ali Group Company

