

GAS RANGE ELECTRIC STATIC OVEN 750mm

GE505D, GE505C

- Heavy-duty construction
- 28 MJ/hr open burners
- Flame failure standard
- Pilot burners optional
- 300mm griddle plate options
- Optional simmer plates
- GN 1/1 5.5kW electric static oven
- Drop down door
- Rear rollers
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



GE505D

Overall Construction

- Galvanized steel chassis
- Welded hob with 1.5mm 304 stainless steel bull nose
- Hob sides 1.2mm 304 stainless steel
- Vitreous enamelled hob control panel
- Splashback 1.2mm 304 stainless steel
- Front panels and oven sides 0.9mm 304 stainless steel
- 63mmdia.heavy-duty1.2mm304stainlesssteeladjustablelegsatfront and two rollers at rear

Cooktop

- Cast iron 28MJ/hr open burners with forged brass cap
- Vitreous enamelled cast iron potstands
- Vitreous enamelled open burner spill covers
- Cast iron simmer plates (optional extra)
- 12mm thick mild steel griddle plates
- 2.5mm 304 stainless steel griddle splash guards
- Stainless steel spill trays
- Aluminised steel internal construction

 $\label{lem:Griddlesections} Griddlesections are standard on RHside. Available on LHside to order or by conversion.$

Oven

- Fully welded and vitreous enamelled oven liner
- GN 1/1 capacity with 4 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Cast iron even heat oven sole plate
- 5.5kW heating elements
- Drop down door
- 0.9mm 304 stainless steel door outer
- 1.0mm vitreous enamelled door inner
- High density fibreglass insulated
- Supplied with two chrome wire oven racks

Controls

- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

Cooktop

- Variable high to low controls to open burners
- Open burners flame failure standard with pilot burners optional
- Variable high to low controls to griddles
- Griddles standard with pilot, flame failure and piezo ignition

Over

- Separate temperature and top heat power regulation controls
- 50-320°C thermostatic control
- Lo-Hi top heat control
- Indicator lights for power and heating

Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Lift off burner heads and vitreous enamelled burner spill covers
- Stainless steel spill trays under open burner and griddle sections
- Removable oven racking and sole plate
- Easy clean vitreous enamel oven and door inner
- Access to all parts from front of unit



GAS RANGE ELECTRIC STATIC OVEN 750mm

GE505D, GE505C

Specifications

Burners

Open Burners 28MJ/hr dual flame ring with simmer rate Griddle Burners 20MJ/hr per 300mm section

Oven Elements

3.75kW bottom heat element 1.75kW top heat element

Gas power

112 MJ/hr, 31.1kW GF505D GE505C 76 MJ/hr, 21.1kW

Electrical requirements

5.5kW

1 phase connection:

230-240Vac, 50/60hz, 1P+N+E, 23A

3 phase connection:

400-415Vac, 50/60hz, 3P+N+E

7.8A 7.8A L1 L2 L3 7.3A

Griddle Plate

300mm Griddle cooking surface 292mm x 475mm, 1387cm2

Oven Dimensions

Width 500mm Depth 590mm Height 385mm Rack size 495mm x 540mm Rack positions 4

Gas connection

R 3/4 (BSP) male

Optional underside connection, please specify when orderina

All units supplied with Natural and LP gas regulator

Dimensions

Width 750mm Denth 812mm Height 915mm

Incl. splashback 1085mm

Nett weight

182kg

Packing data


0.87m3, 240kg Width 795mm Depth 870mm Height 1255mm


Gas types


Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request

Adjustable feet at rear Simmer plates (replaces Potstand) Ribbed griddle plates Joining caps Castors

GE505







MOFFRT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au South Australia

Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





IS09001 Quality Management



Cert. No. 6892

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.01.19/1620

