GGv 5060

ProfiLine





| Gross/net capacity | 486/325 litre |
|---|---------------------------------|
| Ext. dimensions in mm (w/d/h) | 747/791/1864 |
| Int. dimensions in mm (w/d/h) | 610/500/1225 |
| Energy consumption in 365 days / 24 hours (kWh) | 1245 / 3.41 |
| Ambient temperature range | +10°C to +43°C 1 |
| Refrigerant | R 290 |
| Connection Rating | 3.0 A |
| Voltage | 220-240 V~ |
| Cooling system | forced-air |
| Defrosting | automatic |
| Temperature range | -14°C to -28°C |
| Gastronorm | 600 x 400.530 x 325 mm |
| Housing material/colour | stainless steel/stainless steel |
| Door material | Stainless steel |
| Liner Material | moulded polystyrol white |
| Type of Control | electronic controller |
| Temperature display | external digital |
| Fault: warning signal | visual and audible |
| Adjustable Shelving | 4 |
| Shelves, freezer compartment | 5 |
| Height of adjustable legs | 150 - 180 mm |
| Lock | fitted |
| Self-closing door | yes |
| Door hinges | right, reversible |
| Insulation | 70 mm |
| Defrost water drain | yes |
| Gross/net weight | 111/103 kg |
| EAN-Nr. | 9005382196670 |
| | |





 $^{^{\}scriptscriptstyle 1}$ Indicates the ambient temperature at which the device can be operated safely.