





## STANDARD FEATURES

1, 2 and 3 minute cycles Wash capacity of up to 960 glasses per hour Compatible with 365mm to 450mm racks Touchscreen controls providing advanced customisation 0.3HP soft start wash pump Dual chemical pumps Hands-free drainage system with sump and drain pump Stainless steel wash and drain filter basket Customisable auto-drain and self-cleaning functionality Selectable cold rinse\* Adjustable tilting rack slide Independent wash and rinse arms Heavy-duty stainless steel construction

1x 450mm dish rack (600 70081)

1x 450mm cup rack (600 70080)

1x cutlery container (C660503)

1x quick connection kit (all hoses and 1p/15A plugset)

SPECIFICATIONS	
A - Hot Water	

Temperature	65°C
Connection	3/4" male, hose supplied
Pressure	200-500kPa
Flow	20L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.2L per cycle**

25mm

## D - Drainage

notice.


Drain pump flexi-hose

C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.25

Isolating switch must be within 1m of, and not directly behind, the machine

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without

Refer to operator manual for installation instructions



<b>Dimensions</b> Width (mm) Depth (mm) Height (mm) Weight (kg) Volume (m3)	<b>Machine</b> 500 600 780 47	<b>Packed</b> 560 650 915 57 0.33
Water Quality	Min	Max
рН	7	8
TDS	1	135
CI-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

500

\*Requires cold water feed, see Operator Monual for instructions. \*\*Water consumption rates my vary based on site conditions

> TSYR PARTS Watemark Cer Gesa at Global



moffat.com.au | 1300 269 801

Manufactured in New Zealand by Washtech Limited - Distributed in Australia by Moffat PTY Limited © Copyright Washtech Limited / Washtech GM Series-8 / WGM0040 / Feb-25

an Ali Group Company

