



TECHNICAL DRAWING

TEMPERATURE (527) 1900 1200 EXTERNAL WIDTH COATED SHELF 1076 INTERNAL WIDTH 124 INTER IMUM 700





128

HF-127 Split Door Freezer 2 Door

Model Number 97000182

PRODUCT FEATURES

- Stainless steel interior and exterior
- 4 x adjustable shelves with clips per door. (Total 8 Shelves)
- Lockable split Doors
- Programmable Digital controller and display.
- 2 years parts and labour warranty.
- Comes standard with 4 x lockable castors.
- Optional Adjustable legs 150 180mm (Sold separately).
- Additional Shelves 580mm x 520mm & clips (Sold separately)

PRO DUCT SPECIFICATION

Exterior	Stainless steel, Galvanized Steel Powder Coated Rear/Bottom
Interior	Stainless Steel
Storage Capacity Litres	1119L
Outside Dimensions	1200mm (W) x 881mm (D) x 2024mm (H) (Height Includes Castors)
Inside Dimensions	1076mm (W) x 690mm (D) x 1495mm (H)
Refrigerant	R290
AC Supply Voltage	230V AC / 50 Hz / 10 Amp
Weight Net/Gross (kg)	167kg/207kg
Cabinet Lighting	LED Lamp 1 x 7.5W
Ambient Operating Temp	10-43°C
Temperature Control	Electronic -18°C TO -22°C
Electrical Circuit Protection	Thermal P&B Circuit Breaker
Shelf per Door	4 Heavy Duty Shelves

INSTALLATION REQUIREMENTS

rator/freezer should not be located next to ovens, grills or other high heat producing equipment.

se the unit to direct sunlight or higher temperatures *

ow at least 120 cm clearance at the front of the unit for smooth door operation. Also allow at least 30cm clearance from the ceiling to the top of the unit for proper air circulation.

*Refer to manual for full installation & maintenance require



For free 12 month extended warranty, register online within 4 weeks of purchase date, hoshizaki.com.au

Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes. Copyright @ 2025 Hoshizaki Lancer Pty Ltd. All right reserved