



Turbo air

NSW & VIC Rebate Eligible

TOP MOUNT SOLID DOOR

Freezer

MODEL: KF25-1(HC) / KF25-1-N

🚅 FEATURES / BENEFITS 🖳

■ Digital temperature control & monitor system

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon(HC) refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low affect to global warming (ODP-0, GWP-3).

■ Hot Gas Condensate System

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leaking from corrosion, but also prevents the overflow of condensate water.

Self Cleaning Condenser Only at Turbo Air

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. When the dust accumulation is too much, their performance drops quickly resulting in possible spoiling of the contents. The self cleaning condenser keeps the condenser clean and prevents performance system failure by automatically brushing periodically.

■ Exterior & interior of the cabinet

The Turbo Air K-series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. The K-series adds a touch of style to the most refined setting

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

Meat Function

The Meat function allows the compressor to run continuously for up to 2 hours. When activated, the temperature drops quickly. This is ideal when you put new stock and need to chill/freeze it quickly. Also for aging meat and fish to an ideal temperature.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

Fridge holds 1°C ~ 8°C for the best in food preservation



LED interior lighting & fan control (only at Turbo Air)

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

Standard features

- · Anti-corrosion coated evaporator
- Self-contained system
- Standard 125mm, swivel castors with locks on the front set
- Door locks standard

Optional features

- · 125mm castors fitted
- · 180mm,105mm, 80mm castors optional
- Adjustable legs 100-155mm, 70-90mm



WITOO AIT Best Value Commercial Refrigerator

TOP MOUNT SOLID DOOR

Freezer

MODEL: KF25-1(HC) / KF25-1-N

Refrigerant Refrigerant R-290 COMP (HP) 1/3HP POWER INPUT(W) 380 Energy consumption 4.64 AMPS(A) 2.5 Capacity 574 Product Dimension W 640 Product Dimension D 850 Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves 3 LED light yes Temperature range Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater / How many layer of the glass)		
COMP (HP) 1/3HP POWER INPUT(W) 380 Energy consumption 4.64 AMPS(A) 2.5 Capacity 574 Product Dimension W Product Dimension D Product Dimension H Weight Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves 3 LED light yes Temperature range Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	Model	KF25-1(HC)
POWER INPUT(W) 380 Energy consumption 4.64 AMPS(A) 2.5 Capacity 574 Product Dimension W 640 Product Dimension D 850 Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature 35°C Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	Refrigerant	R-290
Energy consumption AMPS(A) 2.5 Capacity 574 Product Dimension W Product Dimension D Product Dimension H Weight Stainless steel SUS 439 & SUS 430 Features Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	COMP (HP)	1/3HP
AMPS(A) 2.5 Capacity 574 Product Dimension W 640 Product Dimension D 850 Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature 35°C Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater / Bas 17pe (Low-e/ Heater / Bas 17	POWER INPUT(W)	380
Capacity 574 Product Dimension W 640 Product Dimension D 850 Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature 35°C Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	Energy consumption	4.64
Product Dimension W Product Dimension D Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	AMPS(A)	2.5
Product Dimension D Product Dimension H 1926 Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Proced Evaporation Temperature control Cooling type Glass Type (Low-e/ Heater /	Capacity	574
Product Dimension H Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Prainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Product Dimension W	640
Weight 80 Stainless steel SUS 439 & SUS 430 Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock yes Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature 35°C Prainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater / FAN COOLING)	Product Dimension D	850
Stainless steel Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range Prainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Product Dimension H	1926
Features SCC (Self Cleaning Condensor) Max GN Pan depth GN Pan Door lock Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Weight	80
Max GN Pan depth GN Pan Door lock Adjustable Shelves LED light Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Stainless steel	SUS 439 & SUS 430
GN Pan Door lock Adjustable Shelves LED light Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Features	SCC (Self Cleaning Condensor)
Door lock Adjustable Shelves 3 LED light Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Max GN Pan depth	
Adjustable Shelves 3 LED light yes Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	GN Pan	
LED light Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Door lock	yes
Temperature range -21°C~-12°C Ambient temperature Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Adjustable Shelves	3
Ambient temperature 35°C Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	LED light	yes
Drainage / Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Temperature range	-21°C~-12°C
Forced Evaporation Temperature control Cooling type Glass Type (Low-e / Heater /	Ambient temperature	35 ℃
Cooling type Glass Type (Low-e / Heater /	- ·	Heater + Soaking Paper
Glass Type (Low-e / Heater /	Temperature control	Digital control
(Low-e / Heater /	Cooling type	FAN COOLING
<u> </u>	(Low-e / Heater /	

Design and specifications subject to change without notice.


Actual Shipping weight may differ due to extra packing materials for product protection.


- Door Locks Standard
- INTERIOR LED LIGHTING STANDARD
- SELF-CONTAINED SYSTEM
- STANDARD 3" SWIVEL CASTERS WITH LOCKS ON THE FRONT SET
- SOLID AND STURDY GRILLE DESIGN





PLAN VIEW (unit : mm)





SIDE VIEW

AUSTRALIA BRANCH

TURBO AIR PTY LTD
www.turboairinc.com.au
1st Floor, Building E
10 Highgate St, Auburn
NSW 2144 Australia
T. 02 9737 9881

