

B+S BLACK SERIES: RF-3

Three Pan Rapid Fryer

Project:	Item:




Standard Features:

- AISI 304 Grade Stainless Steel
- Stainless steel constructed pan with center cool zone 2mm Thick
- Efficient multi-jet target burner
- +/- 3°C temperature recovery differential
- Over-temperature safety cut-out switch
- 40L oil capacity per pan
- · Flame failure fitted as standard
- Stainless steel fish plate and night covers included
- Front access to all components makes service easy
- Pan Dimensions: 510mm L x 510mm W x 70mm H (Height is measured from the base plate to the oil level mark)
- 24 Month Warranty

Options:

- Natural or LP Gas
- Non-swivel rear castors
- Baskets are <u>not</u> included

Specifications:



				970	
ENGTH	DEPTH	HEIGHT	GAS CONSUMPTION (Mj/h)		
(mm)	(mm)	(mm)	NG	LPG	
1875	970	1300	405	405	

Connections:

MODEL

RF-3

GAS (GI)	OIL OUTLET (OO)	SUPPLY PRESSURE (kPa)	
(BSP)	(BSP)	NG	LPG
³¼" (M)	1 ¼" (F)	1.0	2.6

- · Combination control valve with inbuilt regulator is supplied within the unit
- Must be installed by an authorised installer in accordance to AS/NZS5601.01

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.

Approval Number: GMK 10683





