


# specifications

## RF7.UBR.2.GD

ReFlex Series, 2 Door (Glass), Underbench Fridge

Project: \_\_\_\_\_

Item No: \_\_\_\_\_



<b>CABINET</b>	
Doors	2 × self-closing, lockable, double glazed, double Low-E, glass swing doors. LH, RH
Internal door opening	2 × door openings: 560mm high × 355mm wide
Shelves	4 × adjustable height shelves: 395mm wide × 510mm deep Note: Bottom shelves supplied floor mounted, additional shelf clips available on request
Worktop	Total thickness 45mm (0.7mm 304 AISI stainless steel over insulating cyclopentane foamed core)
Material	304 AISI stainless steel interior and exterior
<b>PERFORMANCE</b>	
Max. ambient temp.	40°C
Temperature range	1°C to 4°C (adjustable with SKOPE-connect™ -2°C to 15°C)
GEMS class	4M1
GEMS energy consumption	2.39 kWh/24h
GEMS annual running cost	\$262 p.a. (@ \$0.30/kWh)
<b>ELECTRICAL</b>	
Electrical safety climate class	5
Interior lighting	1 × 400mm, 4W LED light
Power cord	Supplied with 2.6m, 10 Amp plug and lead
Power supply	220-240 Volts a.c. 50 Hz, single phase supply
Current draw	2.0 Amps (includes unit 1.5 Amps)
<b>REFRIGERATION</b>	
Controller	SCS Connect (SKOPE-connect™ compatible)
Connectivity interface	Bluetooth® wireless technology
Refrigeration system	Side mounted, integral, removable refrigeration cartridge (part number ULKCNI-0027)
Refrigerant	R290 / 80g (natural refrigerant)
Nominal capacity	450 Watts
Heat rejection (Avg/peak)	100 Watts/110 Watts
Drainage	No plumbing required

<b>DIMENSIONS</b>		
	External	Internal
Height	855mm*	570mm
Width	1290mm	820mm
Depth	730mm**	530mm
Floor area	0.94m <sup>2</sup>	
Weight	116kg	
Gross volume	248 L	
Net volume	202 L	

\* With supplied castors fitted. See height variation below

\*\* Includes 30mm door handle

<b>Height variation</b>	
Supplied castors	855mm
Supplied height adjustable legs	865mm - 905mm
No castors or legs	720mm

<b>Dimensional tolerances</b>		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5mm	
More than 1 metre	-5mm to +10mm	
	Length of multiple cabinets	
	At each joint	At each end wall
Less than 1 metre	±5mm	+15mm
More than 1 metre	-5mm to +10mm	+15mm

<b>Ventilation requirements</b>	
Top	Not required
Sides	Not required
Back	Not required
Bottom	Not required