## specifications **SC430N** Refrigeration Project: Bottom Mount, 1 Glass Door, Upright Fridge Item No: 660 25 551 258 581 Double-glazed swing door 630 21 296 Illuminated sign -1851 2208 Power cord Electronic controller 5 S Floor clearance Adjustable height feet CABINET DIMENSIONS Doors 1 × self-closing, double glazed, argon-filled, toughened safety glass swing External Internal doors (hinged RH) Heiaht 2208mm\* 1430mm Internal door opening 1 × door opening: 1505mm high × 655mm wide Width 660mm 570mm 5 × adjustable height, full width wire shelves: 560mm wide × 410mm deep Shelves Depth 630mm 525mm Sign Illuminated sign Floor area 0.429m<sup>2</sup> Powder-coat galvanised steel Material Weight 112kg PERFORMANCE Gross volume 420 litres \*Height 2208mm includes castors. Max. ambient temperature 35°C Temperature range 0°C to 5°C **Dimensional tolerances** 65 dB(A) Noise measurement Before installing this cabinet allow the following **GEMS** rating class M1 dimensional tolerances Linear dimensions Overall cabinet dimensions 2.74 kWh/24h GEMS energy consumption Less than 1 metre ±5mm GEMS annual running cost \$300 p.a. (@ \$0.30/kWh) More than 1 metre -5mm to +10mm **ELECTRICAL** Length of multiple cabinets At each joint At each end Electrical safety climate class 5 wall Interior lighting 1 × 7W switched LED strip lighting Less than 1 metre ±5mm +15mm Sign lighting 1 × 11W switched LED strip lighting More than 1 metre -5mm to +10mm +15mm Power cord Supplied with 10 amp plug and 1.7m lead Ventilation requirements Power supply 220-240 volts a.c. 50 Hz, single phase supply Top Not required Current draw 2.3 amps Sides Not required REFRIGERATION Back 100mm Bottom Not required Controller Electronic controller with digital temperature display Refrigeration system Bottom mounted split refrigeration system Refrigerant R290 / 45g (natural refrigerant) Nominal capacity 320 watts Heat rejection (avg./peak) 115 watts/140 watts Drainage No plumbing required

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2020 SKOPE Industries Limited

## SKOPE INDUSTRIES LIMITED

Australia Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673 Email: skope@skope.com, Website: www.skope.com

## PSS0685 Rev. 1.1 Dec. 2021

