

Tabletop model. 10 m³/h. 320 mm.

P/N 1140727



SALES DESCRIPTION

320 mm. sealing bar. 10 m³/h Busch vacuum pump. Vacuum controlled by sensor.

- √ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- √ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- √ "Pause" button.
- √ Phased vacuum programme.
- Detection of the evaporation of liquids.
- √ Double seal.
- √ Cordless sealing bar.
- Progressive decompression.
- √ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- √ NSF-listed model.

INCLUDES

- √ Filling plate
- √ Bluetooth connectivity
- ✓ Inert gas flush
- ✓ Printer connection

SPECIFICATIONS

Pump capacity: 10 m3/h Pump capacity (60 Hz): 12 m3/h

Bar length: 320 mm Total loading: 370 W

Vacuum pressure (maximum): 2 mbar

Electrical supply: 230 V / 50-60 Hz / 1 \sim (3.4 A)

Internal dimensions

- √ Width: 330 mm
- ✓ Depth: 360 mm
- √ Height: 155 mm

External dimensions (WxDxH)

- ✓ Width: 384 mm
- ✓ Depth: 465 mm
- ✓ Height: 403 mm

Net weight: 39.5 Kg

Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

ACCESSORIES

- ☐ Filling plates
- Liquid insert plates
- ☐ Vac-norm external vacuum kits
- □ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- □ Trolley for vacuum packing
- machines
- ☐ Thermal labels for CG2 / RB printer
- ☐ RB Desktop printer for SU vacuum packing machines
- ☐ Thermal transfer labels for RB







Food Service Equiment Manufacturer



Polígono Basarte, 1. 20720 Azkoitia, Spain phone +34 943 15 72 36 sales@sammic.com



Project	Date
Item	Qty
Approved	