



Underbench Storage Refrigerators with Solid Door

Features:

- Self closing stainless steel doors with integrated handles
- Digital controller and digital temperature display
- Dynamic fan forced cooling system with automatic defrosting
- Shelf to fit gastronorm pan size GN1/1
- Stainless steel finish exterior and interior
- Frequency/voltage: 50Hz/220-240 V
- Plastic coated steel shelves
- Lockable engine compartment
- Refrigerant: R290
- Lockable castor wheels
- Ambient temperatures +16°C to +43°C



USC260H



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 314 L

Exterior dimensions in mm: 1360w x 700d x 830h



Number of adjustable shelves: 2

Temperature set range: -2°C to +8°C

Gross/net weight: 119/102 kg

Energy consumption in 24h: 2.2 kWh

USC400H



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 465 L

Exterior dimensions in mm: 1795w x 700d x 830h



Number of adjustable shelves: 3

Temperature set range: -2°C to +8°C

Gross/net weight: 140/121 kg

Energy consumption in 24h: 3.1 kWh

USC550H



Allow min. 100mm clearance for installation, all vents must be left clear

Gross volume: 616 L

Exterior dimensions in mm: 2230w x 700d x 830h

Number of adjustable shelves: 4

Temperature set range: -2°C to +8°C

Gross/net weight: 170/150 kg

Energy consumption in 24h: 4.7 kWh